



## Why Opti-Pro?

Opti-Pro hose reels provide better safety and efficiency when hoses are needed to power tools or equipment. The Opti-Pro hose reel keeps hoses off the floor to reduce the risk of trip or slip hazards. These reels also protect the hose, preventing kinks and other damage, which translates to additional uptime and reduced pressure loss to the tool or equipment. The Opti-Pro hose reel comes with hose installed and includes a 2.5 foot whip hose to connect to your compressed air piping system. Opti-Pro hose reels are also suitable for inert gases, water, (and other fluids, please consult with factory) up to 300psi.

## Standard Features

- 2.5' x 1/2" connecting hose with swivel
- Pre-loaded with Parker 7290 hose
- Four-way pinch free roller system
- Snag free, adjustable hose stop
- Full port, bronze, pressure balanced swivel
- 7 position guide arm
- Heavy duty, fatigue resistant return spring
- Heavy gauge steel pedestal powder coated
- 5 year warranty reel, hose warranty 1 year
- Made in USA

Model	Description	Hose Size	Hose Outlet	Real Inlet	Max Pressure
TP-HR30-06	HOSE REEL, PREMIUM 30' x 3/8"	30' x 3/8"	1/4" MNPT	1/2" MNPT	300 PSI
TP-HR30-08	HOSE REEL, PREMIUM 30' x 1/2"	30' x 1/2"	1/2" MNPT	1/2" MNPT	300 PSI
TP-HR50-06	HOSE REEL, PREMIUM 50' x 3/8"	50' x 3/8"	1/4" MNPT	1/2" MNPT	300 PSI
TP-HR50-08	HOSE REEL, PREMIUM 50' x 1/2"	50' x 1/2"	1/2" MNPT	1/2" MNPT	300 PSI

Model	Description
TP-92-04F	1/4" NPTF Universal Quick Coupler, works with 1/4" body industrial and automotive interconnect plug
TP-92-08F	1/2" NPTF Universal Quick Coupler, works with 1/4" body industrial and automotive interconnect plug
TPFF-08-08	1/2"F x 1/2"F NPT Mini ball valve
TPMF-08-08	1/2"M x 1/2"F NPT Mini ball valve
TP-IV-50-08F	1/2" NPTF Lockable Exhausting valve
TP-HR-SWV	Swivel Bracket, wall mount for horizontal pivot
TP-QMP	Quick Mount Plate, direct mount to strut for I-beam mounting
TP-HR-IBC	I-Beam Clamp for beam widths of 4.5" - 6.5"